

SONORA[®] ULTRAWHITE CEILING TILES

Construction:

6-7 PCF Ecose[®] glass fiber core with high NRC rating.

Thickness: 1", 2"

Size: 2' x 2' (nominal)

Finish: UltraWHITE Fabric

Fire Rating: Class A

Sound Absorption Coefficients (Type E-400 Mounting)							
Size	125Hz	250Hz	500Hz	1KHz	2KHz	4KHz	NRC
1"	0.74	.63	.60	.75	.82	.77	.70



SONORA[®] TEXTURED CEILING TILES

Construction:

6-7 PCF Ecose[®] glass fiber core with high NRC rating.

Thickness: 1", 2"

Size: 2' x 2' (nominal)

Finish: Textured Fabric

Fire Rating: Class A

Sound Absorption Coefficients							
Size	125Hz	250Hz	500Hz	1KHz	2KHz	4KHz	NRC
1"	0.75	.91	.70	.93	.98	1.03	.90



SONORA[®] PVC SEALED CEILING TILES

Construction:

6-7 PCF Ecose[®] glass fiber core with high NRC rating.

Thickness: 1", 2"

Size: 2' x 2' (nominal)

Finish: 2.5 mil PVC Film – Easy to Clean!

Fire Rating: Class A

Sound Absorption Coefficients (Type E-380 Mounting)							
Size	125Hz	250Hz	500Hz	1KHz	2KHz	4KHz	NRC
1"	0.75	.76	.72	1.03	.76	.38	.80

